

# "Manual Cut-Sheet"

for

nsn-2840-01-237-0356

"Flight Safety Critical Aircraft Part"

First Article Rqmt's and Instructions with New Source Qualification Rqmt's for ESA Approval.

(AFMCL64-110 AFMCL22 102 and F	RTICLE REQUIREME	NTS	<i>.</i> .		1. DATE	
2 RIP MIDD NUMBER	(AFMCI 64-110, AFMCI 23-102 and FAR Part 9, Sub Part 9.3) (Additional Instructions on Page 3)					
2. P/R/MIPR NUMBER	3. PART NUMBER 4. NSN 4. NSN 2841					
C FIRST ASSISTANCE	-01-237-0356PT					
5. FIRST ARTICLE QUANTITY						
THE FIRST ARTICLE IS3	UNIT(S) OF LOT/IT	EM	1	<del></del>		
AND WILL BE: PART OF PRODUCTION Q	JANTITY	X :	N ADDITION TO F	PRODUCTION QUAN	TITY	
6. ARTICLES		7. LONG L	EAD TIME ITEMS			
WILL WILL NOT SERVE AS A	MANUFACTURING	R	EQUIRED	X	NOT REQUIRED	
STANDARD			(See FAR 52.209	9-3 or -4, alternate II,	,	
8. SPECIAL REQUIREMENT/PRODUCTION FACILITIES	ISee FAR 52.209-3 or -4 Alt	ernate ()				
X REQUIRED			NOT REQUIRED			
"The First Article offered must be manufacture	ed at the facilities in which t					
component not manufactured by the contractor the contract. A certification to this effect mus	, such component must be m	ianufacture	d at the facilities i	in which the compor	or if the Hirst Article is a ent is to be produced for	
9. TEST/INSPECTION REQUIREMENTS		F.F	IRST ARTICLE DE	I IVERV		
A. X CONTRACTOR TESTING GOVERN	IMENT TESTING	1	ATTICLE DE	- W L I 1 I .		
		(	1) Due within	calendar	days from date contract.	
Performance or other characteristics which the F	irst Articles must meet					
are identified in Pratt & Whitney draw	ring 4068639 and	(	(2) Notify	calendar days	prior to shipment.	
sub-tier drawings and specifications	- ····	(	(3) Delivered to go	overnment at		
B. The detailed technical requirements for First Art	cle approval tests are	-	···	· · · · · · · · · · · · · · · · · · ·		
contained in Block 12 of this form	or approval tosts are	-				
		-	. /\$a	t Forth Consignee and A	1 ddanas	
(Cite Spec and Para number	1	(4			val/disapproval within	
C. X TEST PLAN REQUIRED	,		days after recei	ipt of first article pac	kage.	
(1) DD Form 1423 ELIN						
		G. E		aovernment testing/i	nspection evaluation.	
(2) Delivery due30 calendar days fro			\$			
the same and the same approval	disapproval 43				·	
days.						
D. Contractor's notification to ACO and PCO						
· · · · · · · · · · · · · · · · · · ·	equesting Activity)					
of test time and location due 10 days prior to start of testing.						
E. X TEST REPORT REQUIRED						
· <del></del>						
(1) DD Form 1423 ELIN						
(2) Due $12()$ calendar days from date	of contract.					
(3) Forwarded to PCO and then to USA	F DLA 339 focal					
point, in-turn.						
(4) Government written notice of approval/disa	pproval due <u>60</u>					
days after receipt of contractor's report.						
10. DISPOSITION OF FIRST ARTICLES		L				
			Disapproved Ffirs	st Articles will be ret	urned to the contractor/	
Approved First Articles will be forwarded t	0		will be reta	ained by	pending	
			disposition instru	ictions from the cont	ractor	
(insert quantity).FirstArticles wi	I he expended intention		On purchase re	equests designated	as direct shipments the .	
Residual components of dispproved FirstA		لـــا		_	OTE: Always applicable on	
returned to the contractor. will be re			Foreign Military S	Sales (FMS)).		
	ition instructions from		- 4			
the contractor.			<ul> <li>a. Approved Firs shipment with pr</li> </ul>		urned to the contractor for	
First Articles will be installed on aircraf		rieles will re'- it				
proper fit function. Approved article	as marked above		rticles will remain the same			
aircraft equipment and will not be forwar						
will be considered part of the contract qua		X	Other Disposition	on: See block 1	2 of form	

	LONDI		FIRST ARTICLE APPROVAL				
а.	X	Offerors who have pre-	viously furnished production	quantities of the same ir Force.	or similar article to the p	orime contractor	for delivery to the
b.		Offerors currently in prohave received First Arti	oduction of the same or sim cle approval under the existi	nilar article for a	Government,	DoD,	Air Forceontract and who
C.	X	Offerors who have prev	riously furnished production ovided articles thus furnishe	quantities of the same d, have exhibited satis	or similar articles to the factory performance in si	e X G ervice in the opir	overnment, X DoD, nion of the Air Force.
d.	X	Provided not more than	36 months have ela	psed since completion	of the contract.		
e.		First Article testing will	not be waived.				
f.	X	See Remarks in block 1	2 below.				
	THIS	DECISION. THE BUYE	ORY PERFORMANCE IN SI	ERVICE AND PREPARE RICES <i>(That is, both</i>	AND RETAIN SUPPOR	TING DOCUMEN	WHETHER OR NOT THE ITEM ITATION TO FULLY JUSTIFY article approval) AND MUST PLIED ARTICLE:
	,	A. PROCURING OFFICE	B. CONTRACT NUM	BER C. DATE C	DF CONTRACT D. S	PECIFICATION N	NUMBER AND REVISION
12. F	REMAR	RKS					
9.B.	Fir	st article test require	ements shall include:				
	a.	Verification of all d	imensional and surface	e texture requirem	ents of P&W drawin	ng 4068639 a	nd sub-tier.
	b.	Verification of conf Pratt & Whitney or	ormance to the inspect SA-ALC/LPFE appro	ion requirements oved source for the	of QAD4068638. In specific inspection	nspection(s) s as identified	shall be performed by a in the approved test plan.
	С.	Verification of mate & Whitney or SA-A	erial properties in acco ALC/LPFE approved s	rdance with AMS ource for this testi	4215 and PWA 331 ng as identified in t	. Testing sh	all be performed by a Pratt test plan.
	d.	Verification of conf	formance to PWA 830-	1 and AMS 2470.			
10.	Disp	osition of First Arti	cles:				
	,	Approved first articlathe same as for produceeptance.	e(s) will be retained at uction items. If a firs	the contractor's factorial tarticle is expendent	acility for reconditions and testing, approved	oning (if nece val of first ar	essary) with final acceptance cicle will constitute
	b. 1	Disapproved first art	icle(s) shall be retaine	d at the contractor	's facility, unless sp	ecified other	wise by the PCO.
11.			nived if offeror is the p				•
						•	
13. C		ZANT ENG ORGANIZAT	N RESPONSIBLE FOR CON	DUCTING 14	. PR INITIATOR (Name, (	Organization, Phe	one)
AND	ZA.	OVING TEST (Notice)	organization money				
Jolly	/ Sar	for, SA-ALC/LPFE	(C210) 925 0792				

## **CONTRACT DATA REQUIREMENTS LIST**

(1 Data Item)

Form Approved OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 110 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0701-0188), 1215 Jefferson Davis Highway, Suite 1204, Artington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of the Government Issuing Contracting Officer for the Contract/PR No. listed in Block E.

A. CONTRACT LINE	C. CATEGORY:  TDP TM OTHER									
D. SYSTEM/ITEM F100-PV	W-100/-200 Engin	E. CONTRACT/PR NO. F CONTRACTOR								
1. DATA ITEM NO.	2. TITLE OF DATA ITEM	.03								
A001		S Configuration Management Plan  3. SUBTITLE  Noun: Pre			Nsn-2840-01-237-0356 Front Gearbox Housing Assembly e-Production / First Article Plan				17. PRICE GROU	
4. AUTHORITY (Data Acquir			5. CONTRACT REFEREN	CE	1	6. REQUIRING OFFICE	18. ESTIMATED			
7. DD 250 REQ	CMAN-80858 / T	T 40			70.	DSCR-	JLTB			TOTAL PRICE
SD	REQUIRED	10. FREQUENC	r 1 Time	12. DATE OF FIRST SUBMISSIN	ON	14. DISTRIBUTION			į	
8. APP CODE	_	11. AS OF DAT		13. DATE OF SUBSEQUENT		- ADDOCTOR	b. COPIES			i
N/A	A		N/A	SUBMISSION N/A		a. ADDRESSEE	Draft	Fir Reg	Repro	İ
16. REMARKS				17/21		DCM - QAR	0	O	перия 1	i !
Nsn-2840-01-2	237-0356 , Part# 4	068639 (	77445).			Vendor DCM				
Block 4. Taile	ored:									
The Contract	Awardee shall pro	vide a nla	n for approva	l that angures all	drawina.					
and specificati	on requirements a	re compli	ed with prior	to First Article sa	mple	DSCR-JLPA PCO	0	0	1	
all drawing(s),	Awardee shall pro on requirements a The Plan shall inc , specifications, ar ress the following	id process	requipment ans requirements	d facilities" used . As a minimum.	to verify the	Richmond, VA		-		
Pian snail addi	ress the following	criteria:	-	•	•					
(a). A list of a	Ill drawing dimens	ions, surf	face texture, e	tc, to be inspec	ted and	OC-ALC/LPFRB	0	2	0	
etc An actu	all drawing dimens to be used for ver tal drawing(s) shal the drawing(s) to	l be subn	nitted with the	Plan that correlat	es the	Tinker AFB, OK				
	verify that all non		-							
	verify that all visu						_			1
	verify material properties, and che									
(e). A plan to Original Equip	ensure that all ma oment Manufacture	nufacturii er(OEM)	ng processes a Pratt and Wh	re performed by the itney, certified versions.	he endors.					
(f). A plan to specific forgin	ensure that the for g / casting require	ging / casement, as	sting source is applicable.	OEM approved f	or the	1				:
(g). The Plan process require	shall identify all e ements, as specific	xternal so ed under	ources for appl OC-ALC/LPF	icable material an R source approva	d l.					
(h). The Plan shall identify GFE, GFM, and Tooling requirements if applicable.										
(i). The Plan s organization, p including calib	shall identify all as planning, procedur pration, inspection	pects of or res contro and testing	Quality Assura I, responsibiling related crite	nce such as policities, and interface	les, s					
										Į į
Engineering In	delines for this Planstructions, and Ll	PF-QAR-	001.	MC 1 01111 200,						
Pleak 7 The	"Dec Decderation /	EATE DI			~ .					
evaluation and	"Pre-Production / approval. Copy	shall be s	n" shall be sul ubmitted to the	omitted to OC-AL e local DCM and	C for PCO.					
Block 14. Dis the Plan to;	stribution as follow	vs: Copy	of the contract	shall be provided	l with			-		
·	AR, Vendor DCM	Office	3 00	-ALC/LPFRB						
-		-								
2. Defense Supply Center Richmond (DSCR) Attn: DSCR-JLPA-P1V Tinker AFB, OK 73145-303										
8000 Jeffei	300 Jefferson Davis Highway ichmond, VA 23297-5878									<u> </u>
,	2 22 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2					45 70711				i
G. PREPARED BY	Taxaal Ma	25 y 1A	H. DATE	I. AFFRQVED B	y <del>-</del>	15. TOTAL	J. DATE	2	2	
( Vase	ph' The	by C	07-09-20		Jos Sigh	Perk		-09-20	02	 
DD FORM 1423-	1, AUG 96 (EG)	J	PR	EVIOUS EDITION MAY BE	USED. 4	Designed using Perfo	Page I	of 2 VHS/DIOF		

## **CONTRACT DATA REQUIREMENTS LIST**

(1 Data Item)

Form Approved OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to avarage 110 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. Please DO NOT RETURN your form to the above address. Send completed form to the Government Issuing Contracting Officer for the Contract/PR No. listed in Block E.

A. CONTRACT LINE I	ITEM NO.	B. EXHIBIT	·	C. CATEGORY:						- -
D. SYSTEM/ITEM	TDP			_						
	V-100/-200 Engine	es	E. CONTRACT/PH	NU.	F. CONTRA	TRACTOR				
1. DATA ITEM NO.	2. TITLE OF DATA ITEM	3. SUBTITLE				Nsn-2840-01-237	7 0256			17. PRICE GROU
A002		Test / Inspection Report Noun Fir				: Front Gearbox Ho st Article Test / Insp	using a ection	Assem Repor	ibly t	
4. AUTHORITY (Data Acquiss DI-N	ition Document No.) DTI-80809B / T		5. CONTRACT REFERE	NCE		6. REQUIRING OFFICE	II TD			18. ESTIMATED
7. DD 250 REQ	9. DIST STATEMENT	10. FREQUEN	LY	12. DATE OF FIRST SUBMISSI		DSCR-				
SD	REQUIRED		Time	30DATO		14. DISTRIBUTION	T	1 000150		
8. APP CODE	-	11. AS OF DA	TE	13. DATE OF SUBSEQUENT		a. ADDRESSEE	b. COPIES Final		nal	
N/A	A	See	Block 16	SUBMISSION N/A				Draft Reg Repro		
16. REMARKS				11/21		DCM - QAR	0	0	леріо 1	:
Nsn-2840-01-2	237-0356 , Part# 4	068639 (	77445).			Vendor DCM			1	
Block 4. Tailo										1
The First Artic	ele Test / Inspection	on Repor	t shall satisfy	all the requiremen	ts in the	DCCD H DA DCC				
approved Pre-I must be satisfied	Production / First	Article T	est Plan. All	drawing requiren	nents	DSCR-JLPA PCO Richmond, VA	0	0	1	:
inspections, ma	anufacturing proce	esses, as	well as mater	all the requirement drawing requirements, non-destructivial requirements, perform the first that the sub-vencocesses. A copyhall be included in	The	Nicimonu, VA				
manufacturing	and inspection pro	ocesses a	s well as proc	periorm the of that the sub-ven	dor(s)					:
are OEM(Pratt process sheets	t and Whitney) cer used to manufacti	rtified to	perform the p	processes. A copy	of the	OC-ALC/LPFRB	0	2	0	!
Report.	to manufacti	- C the I'l	721 1 11 11 11 16 2 21	aan oo meruucu III	are rest	Tinker AFB, OK				
Additional guid	delines for the Tes	st Report	are contained	l in LPF-QAR-003				-		
DID-Element	10.2.6.4.2 Test / i	inspection	results. Sha	all include certifica	tion(s)				-	i
of material and be performed b	l process(es), mate by Pratt and Whiti	erial shal nev appro	l be acquired eved sources a	all include certifica and external proce and labs.	ess(es) to					İ
	,	appro	, rea Boarees t							:
Block 7. The	Report shall be su	bmitted t	o OC-ALC/L	PFRB for evaluati	on and					
арргочаг. Сор										
Block 11. Rep	oort is due no later	than 22	O-days after c	ontract award.						1
Block 14. Dis	tribution as follow	s: Copy	of the contrac	ct and drawing(s) s	shall be					
provided with										
	1. DCM - QA					774				
2. Defense Supply Center Richmond(DSCR) Attn: DSCR-JLPA-P1V 8000 Jefferson Davis Highway Richmond, VA 23297-5878										
	•		97-5878							1
	3. OC-ALC/L 3001 Staff I	PFRB Drive								:
	Annex-4, Po Tinker AFE	ost IAG1	-115							!
	Tillker AFE	s, OK /3	0145-3031							İ
										!
										!
										:
							<u> </u>			
1										
C DDEDADED BY		<del>-</del> r	111 200-	T		15. TOTAL	0	2	2	!
G. PREPARED BY	Josephe	Syk	H. DATE	I. APPROVED B	Y Josq	ephy besylt	J. DATI	E		
( losex	sh Neo.	C	07-09-20	002	zezh	1 Oles Je	07	-09-20	002	1
DD FORM 1423-	1, AUG 96 (EG)	-	P	REVIOUS EDITION MAY BE	USED.		Page 2	of 2	Pages	J -

#### **INSTRUCTIONS FOR COMPLETING DD FORM 1423**

(See DoD 5010.12-M for detailed instructions.)

#### FOR GOVERNMENT PERSONNEL

- Item A. Self-explanatory.
- Item B. Self-explanatory.
- Item C. Mark (X) appropriate category: TDP Technical Data Package; TM Technical Manual; Other other category of data, such as "Provisioning," "Configuration Management," etc.
- Item D. Enter name of system/item being acquired that data will support.
- Item E. Self-explanatory (to be filled in after contract award).
- Item F. Self-explanatory (to be filled in after contract award).
- Item G. Signature of preparer of CDRL.
- Item H. Date CDRL was prepared.
- Item I. Signature of CDRL approval authority.
- Item J. Date CDRL was approved.
- Item 1. See DoD FAR Supplement Subpart 4.71 for proper numbering.
- Item 2. Enter title as it appears on data acquisition document cited in Item 4.
- Item 3. Enter subtitle of data item for further definition of data item (optional entry).
- Item 4. Enter Data Item Description (DID) number, military specification number, or military standard number listed in DoD 5010.12-L (AMSDL), or one-time DID number, that defines data content and format requirements.
- Item 5. Enter reference to tasking in contract that generates requirement for the data item (e.g., Statement of Work paragraph number).
- Item 6. Enter technical office responsible for ensuring adequacy of the data item.
- Item 7. Specify requirement for inspection/acceptance of the data item by the Government.
- **Item 8.** Specify requirement for approval of a draft before preparation of the final data item.
- Item 9. For technical data, specify requirement for contractor to mark the appropriate distribution statement on the data (ref. DoDD 5230.24).
- Item 10. Specify number of times data items are to be delivered.
- Item 11. Specify as-of date of data item, when applicable.
- Item 12. Specify when first submittal is required.
- Item 13. Specify when subsequent submittals are required, when applicable.
- Item 14. Enter addressees and number of draft/final copies to be delivered to each addressee. Explain reproducible copies in Item 16.
- Item 15. Enter total number of draft/final copies to be delivered.
- Item 16. Use for additional/clarifying information for Items 1 through 15. Examples are: Tailoring of documents cited in Item 4; Clarification of submittal dates in Items 12 and 13; Explanation of reproducible copies in Item 14.; Desired medium for delivery of the data item.

#### **FOR THE CONTRACTOR**

- Item 17. Specify appropriate price group from one of the following groups of effort in developing estimated prices for each data item listed on the DD Form 1423.
- a. Group I. Definition Data which is not otherwise essential to the contractor's performance of the primary contracted effort (production, development, testing, and administration) but which is required by DD Form 1423.

Estimated Price - Costs to be included under Group I are those applicable to preparing and assembling the data item in conformance with Government requirements, and the administration and other expenses related to reproducing and delivering such data items to the Government.

b. Group II. Definition - Data which is essential to the performance of the primary contracted effort but the contractor is required to perform additional work to conform to Government requirements with regard to depth of content, format, frequency of submittal, preparation, control, or quality of the data item.

Estimated Price - Costs to be included under Group II are those incurred over and above the cost of the essential data item without conforming to Government requirements, and the administrative and other expenses related to reproducing and delivering such data item to the Government.

c. Group III. Definition - Data which the contractor must develop for his internal use in performance of the primary contracted effort and does not require any substantial change to conform to Government requirements with regard to depth of content, format, frequency of submittal, preparation, control, and quality of the data item.

Estimated Price - Costs to be included under Group III are the administrative and other expenses related to reproducing and delivering such data item to the Government.

d. Group IV. Definition - Data which is developed by the contractor as part of his normal operating procedures and his effort in supplying these data to the Government is minimal.

Estimated Price - Group IV items should normally be shown on the DD Form 1423 at no cost.

Item 18. For each data item, enter an amount equal to that portion of the total price which is estimated to be attributable to the production or development for the Government of that item of data. These estimated data prices shall be developed only from those costs which will be incurred as a direct result of the requirement to supply the data, over and above those costs which would otherwise be incurred in performance of the contract if no data were required. The estimated data prices shall not include any amount for rights in data. The Government's right to use the data shall be governed by the pertinent provisions of the contract.

### **ENGINEERING INSTRUCTIONS**

- 1. Full-scale production is not authorized prior to approval of requisite first article test reports by the F100 Fighter Propulsion System Division Engineering Branch (Government Engineering Source Authority (ESA)). Instructions regarding the specific test requirements, number of articles, the disposition thereof, and the conditions for waiver are identified in the First Article Test Requirements for P/N 4068639.
- 2. The inspection methods to be applied to the first articles and production parts shall be documented on inspection method sheets or inspection route sheets and operation sketches which identify the inspection, inspection sequence, significant process parameters, equipment and tooling, gages and acceptance/rejection criteria used. This documentation shall be submitted to the Government ESA through the PCO for approval with the first article test plan and requisite first articles.
- 3. All first articles shall be produced using the same material, processes, equipment, and tooling to be used for manufacture of the production articles.
- 4. The following significant supplies/processes required in the fabrication of first articles and production articles shall be obtained from/performed by the sources approved by the Government ESA as identified in the letter granting engineering source approval. If the letter granting source approval did not document the approved sources, the Supplier shall identify the sources to be employed in the solicitation and provide documented evidence the sources are currently approved by Pratt & Whitney for the respective processes. The Government ESA shall make the determination for approval of the sources identified.

Casting per AMS 4215 and PWA 331 X-Ray Inspection per XRM Code 1 Fluorescent Penetrant Inspection per FPM Code 1 Surface Treatment per PWA 830-1/AMS 2470

- 5. Change of sources for material and significant processes is prohibited without the expressed written consent of the Government ESA. Change in address of a source shall be construed as a change of source.
- 6. The manufacturing methodology applied in the fabrication of the first articles shall be documented on the manufacturing process sheets which identify the processes, process sequence, significant process parameters, equipment and tooling used. These process sheets shall be submitted to the Government ESA through the PCO with the first article test reports.
- 7. All production articles supplied in fulfillment of a Government contract shall be fabricated in accordance with the manufacturing process sheets used in the successful manufacture of the first

article test items. Changes to the operating parameters or sequence of significant manufacturing process prior to the expressed written consent of the Government ESA are prohibited.

- 8. The use of sub-vendors, manufacturing process sheets, or inspection method sheets approved by the Government ESA in no way guarantees the integrity of products/services provided, nor does it relieve the Supplier of the responsibility of delivering components which comply with contractual requirements. The term Supplier, as used in this context, refers to the source contracted by the Government to deliver the finished product.
- 9. Sampling of non-destructive inspections other than dimensional is prohibited.
- 10. Sampling of dimensional inspections of critical characteristics is prohibited.

**END** 

### GENERAL QUALITY ASSURANCE REQUIREMENTS FOR F100 ENGINE FC/DC BREAKOUT COMPONENTS

Page 1 LPF-QAR-001 Rev: D 23 Feb 01

#### 1. APPLICATION.

These requirements apply to all F100 engine Fracture Critical Parts (FCP) and Durability Critical Parts (DCP).

#### 2. PURPOSE.

2.1. This document establishes the minimum technical requirements the Offeror must satisfy to obtain engineering approval of their quality system for FCP/DCP applications. All documentation provided as evidence of compliance with requirements specified herein must be in English and in the Inch-Pound system. Engineering approval of Offeror's Quality Assurance System shall be valid for three years from the date of the OC-ALC letter notifying the contractor of approval.

### 3. REQUIREMENTS.

- 3.1. The Offeror must provide a Quality Assurance Manual that accurately portrays their current quality assurance system.
  - 3.1.1. The Quality Assurance System must meet or exceed the requirements as described in this document and must satisfy one of the following:
    - 3.1.1.1. Certified to ISO 9002 by the American National Standards Institute (ANSI) or the International Standards Organization (ISO) in Geneva, Switzerland, or
    - 3.1.1.2. Previously certified within the last three (3) years to MIL-I-45208A plus paragraphs 3.1 through 3.5, 5.1, 5.2, 6.1, and 6.2 of MIL-Q-9858A by the DCMC or other appropriate government Quality Assurance Representative, or
    - 3.1.1.3. Approved by the Original Equipment Manufacturer (OEM).
  - 3.1.2. Proof of certification/approval must be provided and must be dated within the last three years. The decision to approve or disapprove the Quality Assurance System shall only be made after a thorough review of the Offeror's Quality Assurance Manual by the cognizant engineering authority, OC-ALC/LPFR.
- 3.2. The Offeror must provide OEM documentation identifying the specific conditions/restrictions (i.e., specific P/Ns, components, processes, or material this status applies to, production testing required for material release, testing the supplier is authorized to perform, etc.) imposed by the OEM.
- 3.3. The Offeror must provide proof that their quality assurance plan has placed emphasis upon controlling processes to prevent generation of non-conformances and is supplemented by sufficient inspections or tests to assure effective process control.
- 3.4. The Offeror must provide procedures/specifications governing the control of significant processes proposed for use in the fabrication/repair of the approval item for assuring that:

## GENERAL QUALITY ASSURANCE REQUIREMENTS FOR F100 ENGINE FC/DC BREAKOUT COMPONENTS

Page 2 LPF-QAR-001 Rev: D 23 Feb 01

- 3.4.1. Only Purchaser approved sources are used for raw material, significant processes, and major sub-components and adequate consideration is given to a source's capability and performance prior to placing an order.
- 3.4.2. The quality acceptance standards imposed in routine production acceptance both in-house and by sub-vendors are complete and approved by an OEM and the test methods employed in routine production acceptance are sufficient to verify compliance with these standards.
- 3.4.3. Fabrication performed in-house and by sub-vendors is accomplished in accordance with work instructions specified in manufacturing/repair process sheets, schedules, and/or technical control plans which define the exact sequence of all production operations and all process variables and all critical parameters of manufacturing/repair operations which may directly affect material structure, mechanical properties, surface finish and/or direction or lay of the cutting action. The procedure shall also assure that work instructions have been approved by the customer.
- 3.4.4. All inspection of characteristics, which serves as the basis for final acceptance of a characteristic, including in-process inspections, are performed in accordance with work instructions specified in inspection method sheets which define all characteristics specified on the applicable OEM drawings and Quality Assurance Documents (QAD's), the classification of each characteristic, the Acceptable Quality Level (AQL) for each classification of characteristic, sample size, frequency of inspection, the specific inspection methodology to be utilized, and the required instrumentation. The procedure(s) shall also assure that all inspection method sheets have been approved by the customer.
- 3.4.5. The Offeror must provide evidence that internal and sub-vendor audits have occurred, are adequate to insure quality of the end item and are addressed in the Offeror's Quality Plan. Specific Offeror audit procedures/guidelines which pertain to process and product audits shall, as a minimum substantiate the following:
  - 3.4.5.1. Processes accomplished in-house shall be performed in accordance with work instructions specified in Manufacturing/Repair Process Sheets, Schedules, and/or Technical Control Plans which define the sequence of all production operations and all aspects and parameters of manufacturing/repair operations which may directly affect material structure, grain flow, mechanical properties, surface finish and/or direction or lay of the cutting action. The procedure(s) shall also assure that process sheets have been approved by the Purchaser or the OEM.
  - 3.4.5.2. All inspection of characteristics, which serves as the basis for final acceptance of a characteristic, including in-process inspections, are performed in accordance with work instructions specified in Inspection Method Sheets which define all characteristics specified on the applicable OEM drawings and Quality Assurance Documents (QADs), the classification of each characteristic, the Acceptable Quality Lever (AQL) for each classification of characteristic, sample size, frequency of inspection, the specific inspection methodology to be utilized, and the required instrumentation. The procedure(s) shall also assure that all inspection method sheets have been approved by the Purchaser or OEM.

## GENERAL QUALITY ASSURANCE REQUIREMENTS FOR

Page 3 LPF-QAR-001 Rev: D 23 Feb 01

#### F100 ENGINE FC/DC BREAKOUT COMPONENTS

- 3.4.5.3. Unauthorized changes to work instructions which might directly affect the material structure, grain flow, mechanical properties, surface finish and/or lay of the cutting action or accuracy or reliability of component inspection must be approved the cognizant Fighter Propulsion System, Engineering Source Approval Section prior to production. The procedure(s) shall include responsibility, methods, and procedures for identifying significant changes in inspection methods or criteria, coordination internal approval of such changes, and assuring changes are not introduced in the production cycle without formal Purchaser approval. The procedure(s) must address processes performed by sub vendors as well as those performed in-house.
- 3.4.5.4. Strict adherence to the sequence, parameters, and all other significant process variables of manufacturing/repair operations defined on manufacturing/repair process sheets approved by the customer is maintained both in-house and at sub-vendors' facilities. Specific procedures for auditing and/or controlling requisite significant processes must be provided.
- 3.4.5.5. Dedicated equipment is properly maintained and calibrated IAW ISO 10012-1 and is capable of adequately performing its intended application.
- 3.4.5.6. General housekeeping and manufacturing/repair practices shall be addressed in the Quality Plan to ensure they do not adversely affect the quality of the end product.
- 3.4.5.7. In-process monitoring of principal manufacturing/repair and inspection practices, operating parameters, and process parameters which directly affect material structure, grain flow, mechanical properties, surface finish, lay of the material, and/or critical dimensions, and which are indicators of process effectiveness and efficiency. It shall include responsibility, methods and procedures for identifying variables and parameters to be monitored, developing and approving work instructions, identification of trends which signal process problems, and initiation of corrective actions.
- 3.4.6. Procedures for assuring that certificates of test or conformance provided by sub-vendors of raw material and significant processes are complete and supported by process data and numerical test results from an OEM-approved laboratory for the requisite testing, are representative of material received, and the material is in conformance with Purchaser requirements.
- 3.4.7. Adequate records are retained for documenting sub-vendor lists, sub-vendor quality ratings, layout inspection reports, all Purchaser and OEM approvals, component traceability, and objective evidence of conformance to product, process, and quality acceptance requirements; and are available to the Purchaser upon request.
  - 3.4.7.1. Provide procedures for assuring the traceability of the repair history for repaired components.
- 3.4.8. Evidence of a system for controlling non-conforming material to ensure:
  - 3.4.8.1. The classification of all non-conforming characteristics in terms of critical, major, and minor is approved by the Purchaser.

## GENERAL QUALITY ASSURANCE REQUIREMENTS **FOR**

Page 4 LPF-QAR-001 Rev: D 23 Feb 01

### F100 ENGINE FC/DC BREAKOUT COMPONENTS

- 3.4.8.2. Final disposition of all non-conforming critical and major characteristics including rework and repair is approved by the Purchaser prior to implementation.
- 3.4.8.3. Effective control of non-conforming material at sub-vendor facilities.
- 3.5. The Offeror must provide a specific Quality Plan as described in the applicable quality system of paragraph 3.1 and IAW OC-ALC/LPFR documentation as requested in the specific Qualification Requirement.
  - 3.5.1. The Offeror's Quality Plan shall address specifically how the Offeror intends to ensure the ongoing quality of the approval part and processes required in the manufacture/repair thereof and how this has been accomplished on similar components. The Quality Plan shall include the organization responsible for determining the requirements, factors typically considered in the determination, testing and surveillance conducted on sub vendors, testing laboratories used and the specific testing typically performed, subcontract quality requirements, and the specific paragraphs

of the quality assurance document(s) which govern such aspects. ----- END OF DOCUMENT -----

OC-ALC/LPFR, 3001 Staff Drive, Annex 4, Suite 1AD2-112A, Tinker Air Force Base, Oklahoma 73145-3301, DSN 884-8783, (405) 734-8783

## OC-ALC/LPFR QUALITY ASSURANCE REQUIREMENTS FOR

#### Page 1 LPF-QAR-003 Rev: D 05 Jan 01

#### FIRST ARTICLE TEST PLANS AND REPORTS

- 1. This document provides guidelines for the preparation of first article test plans/test reports for F100 engine parts where referenced within the first article data of a contract.
- 2. FIRST ARTICLE QUANTITY. The quantity of first articles shall be per the contract. The quantity of articles allowed for destructive testing, in accordance with the contract, shall be tested per the first article procedure in its entirety, to include the destructive testing. The remaining articles shall only be tested per the nondestructive portions of the procedure.

#### 3. TESTING REQUIREMENTS.

- 3.1. Testing shall consist of, but shall not be limited to, the verification of the following.
  - 3.1.1. Dimensional conformance including finish requirements.
  - 3.1.2. Conformance to non-destructive inspection requirements (FPI, Ultra-sonic, Eddy Current, X-ray, visual)
  - 3.1.3. Conformance of material properties to include mechanical, metallurgical and chemical.
  - 3.1.4. Conformance to other required processes, specifications, and standards listed on the drawing including sub-tier specifications and standards, special requirements as described in the engineering instructions (EI), quality plans, etc.
- 3.2. First articles shall be serialized. Serial Numbers are to be identified prior to commencement of testing unless otherwise specified.
- 3.3. Dimensional Inspection.
  - 3.3.1. All dimensions, as listed on the assembly drawing and detail drawings, to include drawing notes, shall be measured where possible on all first articles 100% (no sampling allowed).
  - 3.3.2. A tabular format shall be used with drawing dimension, tolerance, measurement, and instrument/gage/tooling/serial number used.
  - 3.3.3. All tooling and gaging used for inspection and acceptance/rejection of first articles shall have calibrations from a laboratory traceable to NIST and in accordance with ISO 10012-1 (formerly MIL-STD-45662), listed in a (tooling & gaging table) table, table shall include nomenclature, serial number, calibration frequency, next calibration date, range, least increment, and accuracy. Listing shall also include alignment tools and constraint fixtures.
  - 3.3.4. Inspection results shall be presented in a table showing the feature measured, dimension and tolerance, actual reading and gage serial number used.
- 3.4. Nondestructive Inspections (NDI), including Fluorescent Penetrant Inspections (FPI), Ultrasonic Testing (UT), Eddy Current (EC), Radiographic Testing (x-ray), and visual inspections, shall meet the following:

## OC-ALC/LPFR QUALITY ASSURANCE REQUIREMENTS FOR

## FIRST ARTICLE TEST PLANS AND REPORTS

Page 2 LPF-QAR-003 Rev: D 05 Jan 01

- 3.4.1. All first articles shall receive 100% of the inspections identified on the QAD. Sampling shall not be allowed.
- 3.4.2. NDI shall be per the applicable specification(s).
- 3.4.3. Sources used shall be Pratt&Whitney approved per the OC-ALC/LPFR letter granting source approval to the contractor.
- 3.4.4. NDI results shall be presented in a table showing the feature inspected, acceptance/rejection criteria used, results and gage/master serial number used. In cases where photographic standards within a VIS specification are applied to an NDI, the inspection report shall include a copy.
- 3.4.5. Inspection Masters/Transfer Masters shall have current calibrations. A copy of the calibration(s) shall be included into the report.
- 3.4.6. Level III or Level II inspectors, as applicable, shall be required. A copy of the inspector's certification(s) shall be included into the report.
- 3.5. Visual Inspections shall include:
  - 3.5.1. Specific visual inspections per a Pratt&Whitney Visual Inspection Standard (VIS) document shall be called out of the applicable VIS and cited as specific inspections.
  - 3.5.2. Visual inspection results shall be presented in a table showing the feature inspected, acceptance/rejection criteria used, results, and gage/master serial number used (as applicable).
  - 3.5.3. In cases where photographic standards within the VIS are used, the inspection report shall include a copy.
- 3.6. Material properties testing shall include mechanical properties, metallurgical properties, and chemical composition tests, as applicable, per the material specifications and the following:
  - 3.6.1. Composition, heat treat condition, and other characteristics/properties, as listed in the technical requirements section, acceptance section, and/or quality sections of the specification(s) so as to verify that the materials and processes are sound, clean, and free of imperfections detrimental to the performance of the part or assemblies.
  - 3.6.2. In some cases a material suppliers certification will not be sufficient and the Contractor shall have redundant testing performed.
  - 3.6.3. Metallurgical microanalysis, as applicable, for raw materials, weldments, brazements, and coatings shall be conducted. Results shall include the complete laboratory report including photomicrographs.
  - 3.6.4. Mechanical testing, as applicable, per manufacturing specifications and the drawing(s).

## OC-ALC/LPFR QUALITY ASSURANCE REQUIREMENTS FOR FIRST ARTICLE TEST PLANS AND REPORTS

Page 3 LPF-QAR-003 Rev: D 05 Jan 01

3.6.5. In cases where the applicable specifications require test reports, these shall accompany the First Article Test Report (FATR).

#### 4. SUBMITTAL.

- 4.1. The First Article Test Plan (FATP) shall be delivered to the Contracting Officer in accordance with the schedule as listed in the contract, or Form DD1423. The FATP shall provide a detailed description of specific testing instructions to be used. Generalized instructions will not be acceptable.
- 4.2. The First Article Test Report (FATR) shall be delivered to the Contracting Officer in accordance with the schedule as listed in the contract, or Form DD1423. All laboratory test results, including those resultant from testing conducted at the contractor's facility and including sub-vendor testing, shall be provided with the FATR in their complete form as provided by the testing laboratory(ies).

#### 5. DISPOSITION OF PARTS.

- 5.1. When required by the contract, the remnants from destructive testing shall be delivered with the First Article Test Report.
- 5.2. When required by the contract and following the completion of non-destructive testing, one article shall be delivered to the Contracting Officer and packaged in accordance with contract requirements. Marking on the package shall be **UNSERVICEABLE Condition Code "R"**. Deliver this part with the First Article Test Report. The other(s) shall be handled in accordance with the contract.

### 6. GENERAL REQUIREMENTS.

- 6.1. All First Articles and all Production Articles shall be fabricated from material whose metallurgical state is in compliance with the drawing requirements, as well as all sub-tier specifications and standards referenced therein.
- 6.2. All First Articles and all Production Articles shall be new manufactured under this contract. No items manufactured under previous contracts shall be delivered without approval.
- 6.3. The subcontractors previously identified by the contractor as sources to be employed, to include laboratory testing, shall be the only sources used. If the contractor wishes to employ a subcontractor other than previously identified, they shall substantiate that the new source is OEM approved for the specific testing required. A change in the address of a source shall be construed as a change of source. Employment of alternate sources shall only be authorized by OC-ALC/LPFR.

 nun take prece	defice over an other t	echinear instructions.
 END OF	DOCUMENT	·····

6.4. Engineering Instructions shall take precedence over all other technical instructions

## QUALIFICATION REQUIREMENTS FOR MANUFACTURING

#### 1. APPLICATION.

1.1 This qualification requirement applies to all F100-PW-100/200/220/E/229 engine Front Gearbox Housings identified in Appendix A.

#### 2. SCOPE.

- 2.1 This document establishes the minimum technical requirements which prospective sources must satisfy in order to obtain engineering source approval for the specified applications. Conditions of waiver are identified in LPF-QR-002. All documentation provided as evidence of compliance with requirements specified herein must be in English.
- 2.2 Engineering source approval shall be valid for three years from the date of the cognizant Government Engineering Source Authority (ESA) letter notifying the contractor of engineering source approval. Approved sources which have not delivered or been contracted by the Government to deliver the approval item during this period shall be required to resubstantiate their capability. Resubstantiation shall involve documenting that no significant changes to process location, sequence, or parameters have occurred, and no significant quality deficiencies are awaiting corrective action. Significant changes or unresolved quality deficiencies may result in additional testing, or revocation of source approval status, depending on the nature and extent of the changes and/or quality deficiencies.
- 2.3 Prospective sources are advised that this component is a durability critical part (DCP).

#### 3. REFERENCE DOCUMENTS

- 3.1 LPF-QR-001: BASIC TECHNICAL DATA PACKAGE REQUIREMENTS FOR FCP/DCP Definitions of terms used are specified in this document.
- 3.2 LPF-QR-002: CONDITIONS OF WAIVER FOR FRACTURE CRITICAL/DURABILITY CRITICAL PARTS
- 3.3 LPF-QAR-001: GENERAL QUALITY ASSURANCE REQUIREMENTS FOR F100 ENGINE FCP/DCP BREAKOUT COMPONENTS

## 4. CONTRACTOR RESPONSIBILITY STANDARDS: (FAR 9-104)

4.1 Offerors must submit a complete technical data package on all similar components as specified in LPF-QR-001.

4.2 Offerors must submit a complete set of drawings as specified in LPF-QR-001.

- 4.3 General standards as specified in FAR 9-104.1 apply.
- 4.4 Special standards as specified in FAR 9-104.2 apply.
- 4.4.1 The specific special standards to be applied are Category 1 Offeror (approval item for P&W) and Category 2 Offeror (similar component for an OEM) as specified in LPF-QR-001.

### 5. PROOF OF CAPABILITY: (FAR 9.105-1, FAR 9.200, & AFLCR 800-10)

- 5.1 Proof of satisfactory manufacture of production quantities of the approval item or a similar component within the last three years for P&W.
- 5.1.1 If approval is sought under Category II, the "similar" component must be a gearbox housing which satisfies the following criteria for similarity:
- 5.1.1.1 Used on the gearbox of a proven high thrust aircraft turbofan or turbojet engine.
- 5.1.1.2 Fabricated of AMS 4215 or similar aluminum alloy. Consideration of similar aluminum alloys is contingent upon the material being characterized by a comparable machinability rating and exhibits the same sensitivity to the process parameters required in manufacturing.
- 5.1.1.3 Illustrates the ability of the Offeror, in conjunction with their subvendors, to:1) perform all requisite significant manufacturing processes and 2) maintain requisite tolerances and surface finishes.
- 5.1.2 Multiple components may be used to demonstrate compliance with 5.1.1 and subparagraphs provided that they satisfy the requirements of 5.1.1 and were produced for an OEM.
- 5.2 The Offeror shall substantiate general proof of capability with documentation which is tailored to the requirements of 5.1 and which satisfies the basic technical data package requirements specified in LPF-QR-001.
- 5.3 Identify all sources of casting per AMS 4215 and PWA 331, anodic treatment, radiographic inspection, and fluorescent penetrant inspection (FPI) to be employed in the production of the approval item for the Government including the specific operations to be performed by each source, and the address of the plant where operations are to be performed. Processes and subcomponents to be performed or produced in-house by the Offeror shall be identified as such. This requirement also applies to Category I Offerors as

well. All sources are subject to approval by the cognizant Fighter Propulsion System Division Engineering Section. Evidence that a proposed subvendor is a P&W LCS Supplier is not in itself sufficient to justify approval. Approval shall be based as follows:

- 5.3.1 The Offeror shall substantiate that the casting source is approved by an OEM for the part number specific casting.
- 5.3.2 The Offeror shall substantiate that sources to be employed for radiographic inspection of casting, including themselves, are approved by P&W to conduct radiographic inspection per XRM Code 1 and are in possession of the latest revisions of P&W specifications XRM Code 1, XRM Master, PWA 331, and applicable gauge and calibration masters. Evidence of approval shall include a copy of the official P&W XRM Quality System certification, the P&W certification of the nondestructive testing technique sheet which includes all restrictions and conditions imposed by P&W.
  - 5.3.3 The Offeror shall substantiate that source to be employed for anodic treatment, including themselves are approved by P&W for AMS 2470.
- 5.3.4 The Offeror shall substantiate that sources to be employed for fluorescent penetrant inspection (FPI), of raw material and finished part, including themselves, are approved by PWA to perform FPI per FPM Code 1. Evidence of approval shall include a copy of the official PWA certification of the FPM Quality System and PWA certification of the nondestructive testing technique sheets, inspection method sheets, or inspection procedures.
- 5.4 The Offeror shall provide evidence that the quality assurance system and available expertise which currently exists within the Supplier's facility, is capable of establishing and maintaining effective process control, and otherwise ensuring the ongoing quality of all material, major subcomponents, and significant processes produced/performed inhouse or by subvendors. Evidence shall comply with the following criteria:
- 5.4.1 A copy of latest document(s) which describe and govern the quality assurance system in effect at the Offeror's facility(ies). If provided within the last year and no significant changes have been incorporated, this requirement may be waived. However, the cognizant engineering activity for the F100 engine, reserves the right to request an additional copy in the event the previous submittal cannot be located.
- 5.4.2 Substantiation that Offeror quality procedures satisfy the requirements of LPF-QAR-001.
- 5.4.3 Samples of contractual requirements previously imposed by the Offeror on sources for castings, surface treatments, nondestructive inspection, and laboratory testing. This requirement may be waived for processes to be performed in-house. In addition, prospective offerors shall provide sample flowdown quality requirements for casting sources, previously imposed on casting suppliers.

5.4.4 Sample reports documenting the results of system, process, and product audits previously conducted by the Offeror in-house and at subvendor's facilities. Sample audit reports shall encompass casting and laboratory testing suppliers. The Offeror shall also specify the frequency of the audits and provide the specific procedures, guidelines, and/or checklists used to conduct the audits.

5.4.5 Sample test reports reflecting overtesting/overinspection conducted by or under the direction of the Offeror, for verifying certificates of test or conformance provided by subvendors, or in-house production. The testing shall verify that certificates are complete and supported by process data and numerical test results from an OEM-approved laboratory for the requisite testing, are representative of material received, and that the material is in conformance with purchaser requirements. Sample test reports shall be provided for casting and correlation of laboratory testing. In event the overtesting is subcontracted, the Offeror shall provide a sample statement of work previously used to obtain testing from an independent laboratory.

## BASIC TECHNICAL DATA PACKAGE REQUIREMENTS LPF-QR-001 FRACTURE CRITICAL/DURABILITY CRITICAL PARTS

Rev: F 28 Dec 00 Page 1

#### 1. APPLICATION.

This specification applies to all F100 engine Fracture Critical Parts (FCP) and Durability Critical Parts (DCP).

#### 2. PURPOSE.

- 2.1. This document is a supplement to established Qualification Requirements (QR) tailored to a specific part(s) for the purpose of defining the basic documentation required of prospective sources to substantiate proof of capability. It is not all inclusive and prospective sources shall note that satisfaction of all requirements defined by the specific QR applicable to the approval part is required to obtain engineering source approval. The basic documentation submitted by prospective sources shall be tailored to the requirements of the specific QR applicable to the approval part which defines specific criteria for proof of capability. All documentation provided as evidence of compliance with requirements specified herein shall be in English and in the Inch-Pound system.
- 2.2. QR's applicable to a specific part shall be made available to prospective sources upon request to OC-ALC/BC or the appropriate Defense Logistic Agency (DLA) activity for parts which are not the subject of open solicitations. Requests concerning the latter shall be addressed to the responsible procuring activity.
- 2.3. Prospective sources are advised that source approval consideration on most Fracture Critical Parts (FCP) is restricted to actual manufacturers of the approval part due to limitations in existing government expertise. Consequently, prospective sources are advised to verify as to whether or not the part(s) in which they are interested fall in this category prior to seeking source approval. Information in this regard may be obtained through OC-ALC/BC at any time or the appropriate DLA procuring activity.

#### 3. DEFINITIONS.

The following definitions shall apply as used in the context of QR's for Fracture Critical Parts and Durability Critical Parts unless otherwise stated in the specific QR.

- 3.1. Approval Part/Item Part/Item for which source approval is sought.
- 3.2. Category 1 Offeror A manufacturing/repair source, which in conjunction with their subvendors has performed all requisite processes on the approval part for Pratt&Whitney. Offerors in this category must provide documentation relevant to the approval part which satisfies all criteria specified under Proof of Capability in their respective QR's with the exception of those identified in 5.1.1, 5.1.2, and 5.2. In all cases the burden of proof shall reside with the Offeror.

FRACTURE CRITICAL/DURABILITY CRITICAL PARTS

28 Dec 00 Page 2

- 3.3. Category 2 Offeror Manufacturing/Repair source, which in conjunction with their subvendors, has performed all requisite processes on a similar part for an OEM. Offerors in this category must provide documentation relevant to a similar part(s) which satisfies all criteria specified under Proof of Capability. In all cases, the burden of proof lies with the Offeror.
- 3.4. Critical Characteristic A part feature which, if non-conforming would result in probable loss of aircraft due to direct part failure or by causing other progressive part failures.
- 3.5. Durability Critical Part A highly stressed part which cannot be completely inspected nondestructively; failure of which will result in a significant maintenance burden.
- 3.6. Fabricate The manufacturing steps necessary for the making of new parts.
- 3.7. Fracture Critical Part A highly stressed part which cannot be completely inspected nondestructively; failure of which will result in loss of aircraft due to non-containment or power loss preventing sustained flight, as a direct result of part failure or subsequent progressive failures.
- 3.8. <u>Inspection Method Sheets (IMS) -</u> document used to describe the steps involved in executing an inspection or series of inspections to include tooling, gages, fixtures, dimensions and other parameters necessary to execute the required inspections(s).
- 3.9. Major Characteristic A part feature which, if non-conforming, could compromise the function of the part, resulting in a significant maintenance burden and/or reduction in weapon system performance.
- 3.10. Manufacturing Process Sheets (MPS) document used to describe the steps involved in executing an operation or series of operations to include tooling, machinery, dimensions, speeds, feed rates, coolants, cutters, tape numbers and other operating and/or set-up parameters necessary to execute the operation.
- 3.11. Material A general term referring to material at any stage in the manufacturing/repair process.
- 3.12. NIST National Institute of Standards and Technology.
- 3.13. Offeror Source furnishing a source approval package in an attempt to obtain engineering source approval to supply the approval part in its finished state to the U.S. Government.
- 3.14. Original Equipment Manufacturer (OEM) Term typically applied to the source responsible for the original design and development of a product or system. In this case it shall refer to sources primarily responsible for the design and development of aircraft gas turbine engines similar to the Pratt&Whitney F100 engine, for a US DoD activity or a NATO country.

Rev: F 28 Dec 00 Page 3

FRACTURE CRITICAL/DURABILITY CRITICAL PARTS

- 3.15. Production Quantities Quantities which establish a reasonable level of confidence in a prospective source's ability to consistently produce parts whose integrity is equivalent to that exhibited by parts which originally passed substantiation testing. As a minimum it shall be considered representative of several production lots or greater quantities commensurate with those specified in current solicitations or annual buy projections and shall be exclusive of quantities produced in experimental or developmental programs.
- 3.16. Purchaser The Purchaser as defined in all applicable government specifications as well as all PWA specifications relative to the part described in this document shall refer to the U.S. Government contracting activity issuing the procurement requirement.
- 3.17. **QRSL** Qualified Repair Source List, the listing of qualified repair sources, located in T.O. 2J-F100-13-1.
- 3.18. Raw Material Ingot, bar, billet, or sheet stock used directly in the fabrication of the finished part or forgings/castings used in the fabrication of the finished part.
- 3.19. Repair The processes and inspections necessary to restore parts to serviceable condition.
- 3.20. Significant Process A process which is capable of producing alterations in the material structure of a part which cannot normally be evaluated without destructive testing and which can compromise the mechanical properties 'and ultimately the reliability of the part. Processes which are considered to be significant by OC-ALC/LPFR are listed in Appendix A.
- 3.21. Similar part A part which satisfies all of the specific criteria for similarity as defined in the QR's for the approval part.
- 3.22. <u>Sub-vendor -</u> A source supplying material, products, and/or services to the Supplier as required in the performance of the contract. This term applies to all facilities other than the Supplier's facility including those of the same company.
- 3.23. **Technical Order -** A technical manual published by the Air Force containing (in this case) technical information required to develop inspection methods and repair processes for aircraft engine parts.

### 4. DOCUMENTATION REQUIREMENTS.

- 4.1. Offerors must submit the following data on all parts referenced within their SAR in addition to data required in the QR:
  - 4.1.1. A complete set of legible drawings for all assemblies, details, and sub-components. All dimensions shall be in the English System of Units.

### FRACTURE CRITICAL/DURABILITY CRITICAL PARTS

Rev: F 28 Dec 00 Page 4

- 4.1.2. A complete set of all specifications (top page only for Pratt&Whitney developed specifications) for all materials and manufacturing/repair processes identified on the drawings for the similar parts and sub-components thereof.
- 4.1.3. Substantiation of possession or the top page of all referenced Pratt&Whitney MCL standards.
- 4.2. Offerors shall include the following documentation on the approval part (Category I Offeror) or similar parts (Category II Offeror) to substantiate Proof of Capability:
  - 4.2.1. Copies of purchase orders from purchaser to Offeror and Offeror to sub-vendors which define quantities ordered and all technical conditions or restrictions imposed. Copies of the most recent shipping documents applicable to the purchase order should also be provided. Shipping documents shall be stamped appropriately by the purchaser to indicate full release where on-site acceptance is specified by the purchase order. In addition, if the part was manufactured/repaired for Pratt&Whitney, the Pratt&Whitney Requirements Control Card and Quality Assurance Document should be provided. The fact that a sub-vendor is a Pratt&Whitney LCS Supplier shall not relieve the Supplier of the responsibility of conducting following-on quality assurance surveillance to ensure that sub vendors are providing conforming material.
  - 4.2.2. A copy of the Manufacturing/Repair Process Sheets (MPS) and Inspection Method Sheets (IMS) employed in the production of the part(s). Evidence of purchaser approval of the MPS is required. Summary of manufacturing/repair operations sheets, travelers, or routing sheets are not acceptable in lieu of MPS, except for some sheet metal parts. In the case of the latter routing sheets which define process sequence, forming tooling, nonconventional machining schedules, weld schedules, and braze schedules shall be provided. All schedules and technical control documents referenced in the MPS which specify process operating parameters shall be included. In all cases where an operation is governed by software, i.e., numerically controlled or automated operations a hard copy excerpt identifying manufacturing/repair process operating parameters must be provided. MPS shall remain confidential and may be stamped "proprietary" at the discretion of the Offeror. Failure to provide detailed MPS and IMS shall constitute grounds for disapproval.
  - 4.2.3. Identification of all sub-vendors of significant processes and sub-components employed in the production/repair of the part(s) including the specific operations and/or subcomponents provided by each sub-vendor.
    - 4.2.3.1. For significant processes subcontracted, the Offeror must provide his method for insuring quality control and conformance to specification at the sub-vendor's plant. This should not only include identification of such procedures in the company Quality Manual but also physical evidence such as audit reports, surveys, and chemical and physical test

Rev: F 28 Dec 00 Page 5

FRACTURE CRITICAL/DURABILITY CRITICAL PARTS

reports. If receiving inspection cannot verify conformance to specification, then chemical and physical test data along with in-work process control data must accompany each lot.

- 4.2.3.2. Repairs performed by sub-vendors shall be accomplished in accordance with work instructions specified in MPS, Inspection Method Sheets, schedules, and/or technical control plans which define the exact sequence of all production operations and all process variables and parameters of repair operations which may directly affect material structure, grain flow, mechanical properties, surface finish and/or direction or lay of the cutting action. The procedure shall also assure that work instructions have been approved by the Purchaser or the OEM specified by the applicable source certification requirements defined in section 6.4 of these OR's.
- 4.2.3.3. Certificates of test or conformance provided by sub vendors of significant processes are complete and supported by process data and numerical test results from and OEM-approved laboratory for the requisite testing, are representative of material received, and the material is in conformance with Purchaser requirements. Acceptance of incoming material based exclusively upon certificates of test/conformance shall be prohibited. Also, generic procedures such as "laboratory testing employed as necessary" are unacceptable. Specific test procedures utilized on wrought engine parts are required.
- 4.2.4. A summary of quality deficiencies experienced in fabrication/repair part during the last two years of production. The summary shall include but not be limited to all Material Review Board (MRB) actions, Quality Deficiency Reports (QDR's), Laboratory Quality Review Orders (LQROs), Supplier Report of Nonconformance (SRONs), Material Deficiency Reports (MDR's) and any other pertinent documentation as well as the coordination of the President and the Quality Assurance Manager. Coordination of the government quality assurance representative shall be included as well if government source inspection was conducted. Actions taken to resolve deficiencies identified including repair, rework or replacement of parts as well as the source primarily responsible for initiating, developing, and implementing corrective actions and the status thereof must also be provided.
  - 4.2.4.1. The quality acceptance standards imposed in routine production acceptance by sub vendors shall be complete and OEM approved and the test methods employed in routing production acceptance are sufficient to verify compliance with these standards.
- 4.2.5. A detailed description of major similarities and differences between the "similar" part(s) and the approval part.
- 4.2.6. A specific description of value added by the OEM to the approval part or similar part(s) including but not limited to performance of manufacturing/repair processes or inspections, supply of raw material, forgings, castings, or sub-components, quality assurance surveillance of sub-vendors of significant processes, use of OEM tooling, fixtures, gages, or inspection master hardware, and use of OEM MPS, IMS or other process related data not referenced on part drawings. The Offeror shall demonstrate capability to fulfill "value added

Rev: F 28 Dec 00 Page 6

FRACTURE CRITICAL/DURABILITY CRITICAL PARTS

" by Pratt&Whitney on the approval part as determined by OC-ALC/LPFR, as the cognizant Fighter Propulsion System Division Engineering Section.

- 4.2.7. A copy of summary of manufacturing/repair process sheets, travelers, or routing sheets which identify all significant manufacturing/repair processes to be employed in the fabrication/repair of the approval part for the U.S. Government. This documentation is subject to approval by OC-ALC/LPFR. As such, it shall include a provision for coordination on each page.
- 4.2.8. Identification of all proposed changes to the MPS and IMS submitted by Category I Offerors, as proof of capability. This requirement applies regardless of whether are not they are considered to be significant changes by the Offeror.
- 4.2.9. The Offeror must provide documentation to prove that their quality assurance system meets or exceeds the requirements as described in the attached document LPF-OAR-001.
- 4.2.10. If an Offeror has had a Quality or Process audit performed by the DoD or agent for the DoD in the last 3 years, the Offeror shall provide the findings and evaluation/rating.

#### 5. SAR FORMAT.

5.1. Source Approval Requests (SAR's) should be submitted in a binder to preclude the loss of contractor data in handling. A hard or semi-hard cover notebook form (i.e. a three-ring binder or similar product), with a table a contents and tabs corresponding to the table of contents is preferable. This will significantly reduce the turn-around time for engineering evaluation as well as reduce the likelihood of oversight or loss of valuable data that could have a significant bearing on the outcome of the evaluation.

**END** 

FRACTURE CRITICAL/DURABILITY CRITICAL PARTS

## 28 Dec 00

## Page 7

#### APPENDIX A

#### SIGNIFICANT PROCESSES

The following examples are typical processes considered significant in that they are capable of producing alterations to material structures, mechanical properties, and ultimately, item reliability, if performed improperly, and cannot normally be evaluated without destructive testing.

- 1. Casting Processes
- 2. Forging Processes
- 3. Heat Treatment and Surface Hardening Processes
- 4. Broaching
- 5. Grinding
- 6. Drilling, Reaming, and Boring
- 7. Milling
- 8. Finish Turning
- 9. Electrochemical Machining Processes (Cavity Sinking, Drilling, Grinding, etc.)
- 10. Chemical Milling
- 11. Electro-Discharge Machining
- 12. Electro-Stream Drilling
- 13. Laser Beam Metal Removal Processes
- 14. Electron Beam Metal Removal Processes
- 15. Peening Processes
- 16. Welding
- 17. Brazing
- 18. Metal Electroplating Processes
- 19. Coating Processes
- 20. Surface Finishing Processes (Honing, Sutton Barrel, etc.)
- 21. Cleaning of Titanium
- 22. Non-Destructive Testing such as: Magnetic Particle Inspection, Eddy Current, X-ray, Sonic, Fluorescent Penetrant

# CONDITIONS OF WAIVER FOR FRACTURE CRITICAL/DURABILITY CRITICAL PARTS

Rev.: B 28 DEC 00 PAGE 1

#### 1. APPLICATION.

- 1.1. This document applies to all qualification requirements for F100 engine parts designated as Fracture Critical or Durability Critical or as otherwise noted.
- 1.2. This document shall only apply to Category I Offerors. This restricts the availability of this waiver to those Offerors who have manufactured/repaired the actual approval part for its Original Equipment Manufacturer (OEM).
- 1.3. It does NOT provide conditions of waiver for the requirement for pre-award qualification of prospective Offerors. It is limited in scope to the specific elements of the qualification requirements specified herein.
- 1.4. Definitions of terms used in this document are located in LPF-QR-001.

#### 2. CONDITIONS.

- 2.1. The requirement that the Offeror must have fabricated/repaired production quantities of the approval part for the OEM within the time period specified by the applicable qualification requirements may be waived in favor of a longer period of time provided that all of the following conditions are satisfied and documented by the Offeror:
  - 2.1.1. There are NO outstanding quality deficiencies of significance.
  - 2.1.2. There were NO significant quality deficiencies in the parts produced/repaired. This must be supported by a summary of all quality deficiencies experienced in the last two years of production/repair for the OEM with the coordination of the Offeror's Plant Quality Assurance Manager and either the Plant Vice President or the Plant General Manager.
  - 2.1.3. There was NO significant value added by the OEM as described in LPF-QR-001. The Offeror shall also account for all significant processes that they did not perform on parts delivered to the OEM by identifying the source that performed the processes.
  - 2.1.4. There have been NO significant changes in Manufacturing/Repair Process Sheets since the part was last produced/repaired for the OEM. Significant changes shall include but are not limited to changes in the following: Processes used, process sequence, equipment used, tooling design, processing location, and principal operating parameters. The Offeror shall provide the following documentation as substantiation:
    - 2.1.4.1. A copy of the OEM-approved manufacturing/repair process sheets employed in the production/repair of parts for the OEM
    - 2.1.4.2. A copy of the proposed manufacturing/repair process sheets for use in the production/repair of parts for the U.S. Government.
    - 2.1.4.3. A facilities list identifying all equipment in-house at the time the parts were in production/repair for the OEM.

# CONDITIONS OF WAIVER FOR FRACTURE CRITICAL/DURABILITY CRITICAL PARTS

Rev.: B 28 DEC 00 PAGE 2

- 2.1.4.4. A current facilities list identifying all equipment in-house.
- 2.1.4.5. Identification of special tooling and gaging employed in the fabrication/repair and inspection of the parts for the OEM and evidence that it is still serviceable and in the possession of the Offeror or can be duplicated.
- 2.1.5. The time period specified by the qualification requirements shall not be waived for similar parts or for approval parts manufactured/repaired for sources other then the OEM.
- 2.1.6. The requirement for a specific quality plan, if required by the applicable qualification requirements, shall not be waived.

**END**